

ZEPROLIN GW

Polymer based Water Sequestrant

Chemical composition	Polymer condensated with sequestrants
Activity	ca. 98 %
Appearance	Pale White free flowing Hygroscopic powder
pH - value 1 : 10	7.5 – 8.5
Charge	Anionic
Shelf life	Up to 1 year from the date of manufacture
Dilution	To be diluted in water 1: 5 and added to drum

Field of application:

Multifunctional use from raw to dyeing.

Properties :

- » ZEPROLIN GW provides Even and Deep Penetration of dyes and avoids dye patches .
- » Provides full uptake of fatliquors and syntans .
- » Reduces the water hardness predominantly thereby helps uptake of all tanning auxiliaries.
- » Provides even shade dyeing with luster for Suedes and Drum Dyed Leathers.
- » Provides inner softness with roundness even in thick leathers.

Usage Quantities:

In Chrome Tanning : 0.5% – 1.5% ZEPROLIN GW
 In Retanning & Fatliquoring : 0.5% – 1.5% ZEPROLIN GW
 In Dyeing : 0.5% – 1% ZEPROLIN GW

Note : The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and application of the product will remain same.
 Store within 5°C to 35°C in original pack with tightly closed.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.

ZSIVIRA CHEMIE MERK PRIVATE LIMITED

www.zsiviraindia.com | info@zsiviraindia.com