



DYNAMOL SWP

Waterproof Fatliquor

Chemical composition	Blend of Hydrocarbons, Esters with Hydrophobic waxes
Appearance	Off White Paste
pH - value 1 : 10	6.5 – 7.5
Active Content	50 to 55%
Charge	Anionic
Stability to electrolytes	Stable to acids and salts under usual tannery conditions. Not Stable in chrome liquors
Shelf life	Up to 10 months from date of manufacture
Dilution	Combinations with other fatliquors have to be stirred thoroughly before dilution. Dilution method: 1 : 3 with water of 50 – 60° C.

Field of application :

DYNAMOL SWP is used to produce High Quality Water Proof and Water Repellent Leathers.

Properties :

- » DYNAMOL SWP provides excellent Water Proof and Water Repellent Character to the leathers.
- » It can be used as a single fatliquor for Water Proof and also for soft gloves and garments and provides remarkable softness with stretch.
- » Best for wet white tanning and pastel shade dyeing.
- » Doesn't highlight the defects on the leather surface.
- » Excellent Light Fastness & Heat Resistance.
- » For Best water proofing effect capping with mineral tanning salts in fresh bath after washing is suggested.
- » It is advised to avoid hydrophilic products in the tanning to get required water proof effect.

Usage :

Pre Fatliquoring	: 5%
Garment Nappa	: Upto 10%
Water Proof Leathers	: Upto 15%
Main Fatliquoring	: 5%
Gloving	: 5%

Note : The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and application of the product will remain same.
Store within 5°C to 35°C in original pack with tightly closed.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.