



ZYTHANE S85M

Aliphatic Matt Polyurethane Dispersion

| | |
|----------------------|---------------------------------------|
| Chemical composition | Matting agents with Polyurethane |
| Appearance | Milky Emulsion |
| Solids | 24 ± 1% |
| Charge | Anionic |
| pH 10% | 9.0 – 9.5% |
| Film Character | Matt |
| Shelf Life | 6 months from the date of manufacture |

Properties & Application:

- » ZYTHANE S85M is used for top coats to provide tough and flexible film with Natural look.
- » Provides Excellent cold crack, abrasion and scuff resistance.
- » Excellent Light Fastness.
- » Can be blended with other PUs to get the required touch and optique.
- » Compatible with acrylics, proteins and other general auxiliaries including cross linkers.

Note: The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and application of the product will remain same.
Store within 5°C to 35°C in original pack with tightly closed.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.

ZSIVIRA CHEMIE MERK PRIVATE LIMITED

www.zsiviraindia.com | info@zsiviraindia.com