

REZINE RP63

Soft Resin Binder for Embossing articles

Chemical composition	Proprietary Acrylic Co-Polymer
Appearance	Milky Emulsion
Solids	33 to 35%
pH 10%	6.0 – 8.0
Charge	Anionic
Film	Very Soft, Elastic and Continuous

Properties:

- » REZINE RP63 gives clear colourless and flexible film.
- » Provides Stretchy film without break even after milling.
- » Excellent Penetration property
- » Very good cold crack resistance.
- » Outstanding Wet and Dry Rub Fastness.
- » Maintains soft touch and natural look.
- » Can be used in Base Coats, intermediate coats in finishing of shoe softy, uppers, garments, gloves and milled articles.
- » Withstands heavy heat and pressure during embossing operation.

Usage :

Recommended 100 to 300 Parts in base coats and intermediate coats.

Note : The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and application of the product will remain same.
Store within 5°C to 35°C in original pack with tightly closed.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.

ZSIVIRA CHEMIE MERK PRIVATE LIMITED

www.zsiviraindia.com | info@zsiviraindia.com