



ZSIVITAN CP

Special Polymer for Hydrophobic leathers

Chemical composition	Polymeric product of carboxylic acid and esters
Solids	Approx 40%
Appearance	Slight Pale Fluid
pH - value 1 : 10	6.5 – 7.0
Charge	Anionic
Shelf life	Up to 1 year at temperatures between 5 and 40° C.
Dilution	Added Undiluted

Field of application

Special polymer for use in post tanning treatment process including water proof leathers.

Properties

- » ZSIVITAN CP is a versatile high performance polymer used for dispersing and filling and enhances the performance of post tanning treatment processes and makes them workable in controlled manner.
- » ZSIVITAN CP Can be used in Neutralization, wet-back, retanning and fatliquoring.
- » ZSIVITAN CP is used in water-resistant leather such as shoe upper and car upholstery along with water proof fatliquors.
- » ZSIVITAN CP has excellent light fastness property and resistant to yellowish even at very high temperature plating.
- » ZSIVITAN CP has very low fogging value and hence suitable for automotive leather.
- » ZSIVITAN CP has good filling of loose portions.
- » ZSIVITAN CP helps the penetration of dyes and avoids spot formation and dye patch.

Note : The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and application of the product will remain same.
Store within 5°C to 35°C in original pack with tightly closed.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.

ZSIVIRA CHEMIE MERK PRIVATE LIMITED

www.zsiviraindia.com | info@zsiviraindia.com