



# ZSIVILAC ECS

Dual Lacquer

<b>Chemical composition</b>	Nitrocellulose with Solvents and Emulsifiers
<b>Solids</b>	Approx 25%
<b>Appearance</b>	Clear Oil
<b>Film</b>	High Glossy, Soft, Stretchy
<b>Shelf life</b>	Up to 6 months at temperatures between 5 and 40° C.

## Properties and Application

**ZSIVILAC ECS** is a high shine dual lacquer based on Nitrocellulose, soluble in both solvent and water. It produces soft glossy film and does not produce grain harshness.

**ZSIVILAC ECS** withstands both high temperature and very low temperature and also doesn't cause blushing even at temperatures below zero degree which is the added advantage due to the high grade raw materials used.

**ZSIVILAC ECS** shall be diluted up to two times of its *weight* with water or solvent/ thinner on "OIL IN WATER" type depending upon the gloss required. It is not advisable to use mixed low grade solvent/ thinner as it will affect the nature of the product and its usage and may cause coagulation during dilution.

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery.

**ZSIVIRA CHEMIE MERIK PRIVATE LIMITED**

Reviewed on 01/10