



## ZSIWAX S56

Pullup/Cruch wax Emulsion

<b>Chemical composition</b>	Emulsion of Hard Polymers Blend
<b>Solids</b>	Approx 30%
<b>Appearance</b>	Pale White Liquid
<b>pH - value 1 : 10</b>	7.5 – 8.0
<b>Charge</b>	Anionic
<b>Shelf life</b>	Up to 6 months at temperatures between 5 and 40° C.

Note : The product being combination of various raw materials, there are Chances of variations in colour and viscosity. The property and Application of the product will remain same.

### Properties

ZSIWAX S56 produces very hard crunch effect with pullup and darkening effect.

### Application:

ZSIWAX S56 is generally diluted with water 1:1 ratio.

For more darkening effect with smoothness it is recommended to mix ZSIWAX S56 with ZOIL 893A in the ration of 4:1 and then dilute with water in the ratio 1:1 .

ZSIWAX S56 is compatible with other waxes and water soluble oils.

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery.

**ZSIVIRA CHEMIE MERK PRIVATE LIMITED**

01/10