



ALDOX PAL

(Polyaldehyde)

Composition of Chemicals	Poyaldehyde
Appearance	Clear Liquid. Possibility of little colour change on storage for long time.
Solids	42% to 45%
pH	4.5 to 5.5
Charge	Amphoteric
Shelf Life	10 months from the date of manufacture

Technology :

ALDOX PAL is a new generation product whereby the aldehyde is Cross linked and Polymerised to give more suppleness without affecting the grain smoothness.

Character :

- » ALDOX PAL is used from pre-tanning to re-tanning of all types of leathers.
- » Catalyses the chrome and improves its exhaustion and uptake thereby providing leather with fullness and softness and reduces the chance of loose grain.
- » In Vegetable tanning, it increases the penetration of the veg extracts and improves its spreading throughout the leather.
- » Improves the strength of the leather and takes care of dye penetration and even dye distribution with dye brilliancy.
- » Best for wet white and washed articles.
- » Improves the tear strength as it neutralizes the inert acid inside the fibres and fibrils.
- » DONOT CONTAIN ANY FORMALDEHYDE or FREE FORMALDEHYDE.

Application :

In pre-tanning	: 2% - 4%
In Chrome Tanning	: 3% - 4%
In Neutralising	: Upto 3%

Note : The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and application of the product will remain same.
Store within 5°C to 35°C in original pack with tightly closed.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.

ZSIVIRA CHEMIE MERK PRIVATE LIMITED

www.zsiviraindia.com | info@zsiviraindia.com